

TECHNICAL DATA SHEET

Hypoid Gear Multi-Purpose GL-5 85W-140

(08/06/2021 edition)

<u>AMALIE Hypoid Gear Multi-Purpose GL-5 85W-140</u> is a premium gear lubricant for light and heavyduty axles. Features include excellent thermal and oxidation stability, compatibility with seal materials, demulsibility, foam suppression, and superior storage stability. In addition, the AMALIE Hypoid Gear Multi-Purpose GL-5 85W-140 gear oil has exceptional EP protection and durability. With all this it is also the most price/performance competitive system used in the industry; it exceeds the performance needs of OEM final drive builders calling out API GL-5.

Benefits

- Excellent EP and Anti-Wear Properties
- Strong Resistance to Oxidation
- Protects Against Rust and Corrosion
- Excellent Water Handling Characteristics
- Compatibility with Seal Materials

Typical Physical and Chemical Properties

Viscosity Grade	85W-140
Kinematic Viscosity @100°C, cSt	28.0
Kinematic Viscosity @40°C, cSt	380.0
Viscosity Index	100
Flash Point, °C (°F)	265(509)
Pour Point, °C (°F)	15(5)
Density, S.G	0.904
Brookfield Viscosity, -12°C, cP	<80,000

Recommendations

AMALIE Hypoid Gear Multi-Purpose GL-5 85W-140 Gear Oil is recommended for gear boxes and transaxles that call for GL-5 gear oil.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.